

HF850 TX/RX

8 m two-part LF/HF Fibreglass Antenna

- High quality 8 m high HF antenna for professional use
- Designed for GMDSS installations
- Rugged design
- Chrome plated solid brass joints
- Designed for rail mounting
- Side fed via open single wire
- Full omni-directional radiation pattern

Electrical Specifications:

Frequency	1.4 - 30 MHz (MF and HF)
-----------	--------------------------

Polarisation	Vertical
--------------	----------

Max. Input Power	1200 W PEP
------------------	------------

Static Capacitance	100 pF
--------------------	--------

Insulation Resistance	10 GOhm
-----------------------	---------

Electric Length	6820 mm
-----------------	---------

Mechanical Specifications:

Color	White
-------	-------

Height	8.2 m
--------	-------

Diameter	Ø 40 to Ø 5 mm
----------	----------------

Mounting	Rail Bracket Kit (Large) P/N 10000-163 (Not supplied!)
----------	--

Mounting place	On rail or pole (Ø 30 - 90 mm)
----------------	--------------------------------



Mounting instruction	Supplied
Materials	PU-painted heavy duty glass-fibre tubes and chromed solid brass
Survival Wind Speed	55 m/s
Operating temperature	-40C to +60C
Connector	Screw terminal
Cable	No cable supplied (Use open single wire)
Serial no.	On product label



Ordering information:

P/N	13802-001 (Without brackets)
-----	------------------------------

Packaging Information:

Type	Polybag
Size	4800 mm
Weight	Approx. 7.0 kg



Mounting



