

## Navtex Tri-Band

### Active low-profile 3-band Navtex antenna for 1" threaded pole mounting

- Active 3-band Navtex (Navigational Telex) antenna
- Low-profile end-fed multiband antenna design
- No groundplane needed
- Mounting kit for mounting on G1"-11 threaded pole or bracket included
- Dedicated Power supply available (not supplied)



#### Electrical Specifications:

Frequency	0.49 MHz, 0.518 MHz, 4.2095 MHz (NAVTEX)
Impedance	50 Ohm
Polarisation	Vertical
Bandwidth	10 kHz, 10 kHz & 150 kHz
Max. Power	10 dBm (Output)
Supply voltage	6 - 12 VDC (Approx. 10.5 mA at 10 VDC)

#### Mechanical Specifications:

Color	White and chrome
Height	Approx. 315 mm
Weight	Approx. 200 g
Mounting	On 1" threaded pole (G1"-11 thread) with supplied 1" Revolving Nut
Materials	PE, PCB, copper, PTFE and chrome plated solid brass
Operating temperature	-40C to +70C
Connector 1	UHF-female
Cable	No cable supplied
Mounting place	On mast
Mounting Instruction	Included
Ingress Protection	IP66
Serial no.	On product label



Ordering information:

P/N	16201-431 (Antenna + 1" Revolving Nut - in Polybag)
P/N	16201-432 (Antenna + 1" Revolving Nut - in Carton tube)

Packing information:

Packing	Individually packing in Polybag or Carton Tube (See "Part No.")
Size	Approx. 0.45 m
Weight	Approx. 0.3 kg

